

BOXP™

A GLOBAL BRAND, MADE IN INDIA.

BM30LR PORTABLE THERMAL PRINTER (LABEL & RECEIPT)



PRODUCT FEATURES

- Multiple 1D Barcode printing
- Supports 2D Barcode printing including QR Code and PDF417
- NVLOGO image download and printing
- Compatible with Windows, Linux, Android, and iOS
- Multi-Language support



FOR TECHNICAL SUPPORT
1800 8899 246

CCC FC CE CB

www.boxp.in

SPECIFICATIONS

Model : BM30LR	Label print mode	Receipt print mode
Printing method	Direct Thermal	
Emulation	ESC/POS	TSPL
Resolution	203 DPI	
Max.print speed	70 mm/s	
Max.print width	72 mm	
Printing specifications		
Storage	Memory:128KB / FLASH:512 KB+8MB	
Monitor	0.96", 128×64 OLED	
Button	Power button, Feed button	
Media		
Media type	Continuous paper, label paper, black label paper	
Media width	25~80mm	
Paper thickness	0.06~0.14mm	
Media roll diameter	50 mm	
Paper exit method	Tearing off	
Fonts/Graphics/Symbologies		
Character size	Simplified Chinese (GB18030): 24 × 24, Traditional Chinese (BIG5): 24 × 24, Japanese (SHIFT-JIS): 24 × 24, Korean (KSC5601): 24 × 24, English characters FONTA: 12 × 24, English Character FONTB: 9 × 17	
1D Barcode	UPC-A/UPC-E/JAN13 (EAN13) / JAN8(EAN8)/CODE39/ITF/CODABAR/ CODE93/CODE128	CODE128, EAN128, ITF, CODE25, CODE39, CODE39C, CODE39S, CODE93, EAN13, EAN13+2, EAN13+5, EAN8, EAN8+2, EAN8+5, CODABAR, POSTNET, UPC-A, UPCA+2, UPCA+5, UPCE, UPCE+2, UPCE+5, MSI, MSIC, PLESSEY, ITF14, EAN14
2D Barcode	QR CODE / PDF417	
Character enlargement/rotation	Magnify 1-8 times, rotate (0°C, 90°C, 180°C, 270°C)	
Physical Features		
Dimension	123 × 110 × 62mm(D×W×H)	
Weight	340g	
Operation	6~40 °C, Humidity: RH 20 ~ 90%	
Storage environment	-25 ~ 55 °C, Humidity: RH 20 ~ 93%	
Power Input	DC 5V / 2A	
Battery	DC 7.2V / 2550mAh	
Charging time	3 hour, 58min	
Standby time	95 hour, 48min	
Printing battery life	3 hour, 47min	
Operating system	WINDOWS/ Android / IOS / Linux	